



Cubic bollard

Pathway Lighting

Bollard 680 mm high with anti-glare light emission, designed for use in pedestrian circulation, commercial areas, hospital projects, etc.

Certifications:



Warranty:

5 Years

General technical data:

Light source	Built-in LED
Nominal luminous flux (lm)	220
System Efficacy (lm/W)	>24
CCT	4000K
CRI	70
Beam angle	65°
Power	9W
Input voltage	127-220V~
Input Frequency	60 Hz
Power factor	>0.85
Total Harmonic Distortion (THD)	<10%
Operating Temperature	-10 to 40 °C
Driver	Integrated
Control	0-10V
Lifespan / LED maintenance	25,000 L70
Housing	Aluminium
Lens material	PMMA (Acrylic)
Finish	Electrostatic painting
Color	Grey
IP	65
IK	05
Mounting type	Surface mounting

Order information:



Code construction example:
UU 9047 G BN B

Application	Consec.	Color	CCT	Input voltage	Power	Nominal luminous flux	CRI	Beam angle	Dimensions
UU	9047	G- Grey	BN- 4000K	B- 100-220V~	9W	220	70	65°	150*150*580mm


Energy efficiency:

CODE	Nominal luminous flux (lm)	Power (W)	System Efficacy (lm/W)
UU 9047 G BN B	219	8	27.76

Input current:


Power (W)	Input current
8	0.07-0.041 A

Photometric:



Cubic bolardo 65°

Product dimensions:



Cubic bolardo 9W

Downloads:

[Go to downloads section](#)