



## Performa Pro

### High power downlight

It is a unique solution in its type since it is a downlight for general lighting of up to 100W of power, created to offer lighting levels for a double or triple height; it also has a 0- 10V control protocol and an optical design based on a specular aluminum reflector that favors the control of the light.

Certifications:



Warranty:

5 Years

#### General technical data:

Light source	Built-in LED
Nominal luminous flux (lm)	4,000
System Efficacy (lm/W)	>85
CCT	3000K / 4000K / 5000K
CRI	80
Beam angle	60°
Power	40W
Input voltage	127-277V~
Input Frequency	60 Hz
Power factor	> 0.90
Total Harmonic Distortion (THD)	< 10 %
Operating Temperature	-10 to 40 °C
Driver	Integrated
Control	0-10V
Lifespan / LED maintenance	50,000h L70
Housing	Aluminium
Lens material	PMMA (Acrylic)
Color	White
IP	4X
IK	04
Mounting type	Recessed

### Order information:



Code construction example:  
UO 1200 B BN A

Application	Consec.	Color	CCT	Input Voltage
UO	1200	B- White	BC- 3000K BN- 4000K BF- 5000K	A- 127-277V~

Power	Nominal luminous flux	CRI	Control	Beam angle	Dimensions
40W	4,500	80	0-10V	60°	241*170 mm


## Energy efficiency:

CODE	Nominal luminous flux (lm)	Power (W)	System Efficacy (lm/W)
UO 1200 B BC A	3,815.00	40.00	95.37
UO 1200 B BN A	3,815.00	40.00	95.37
UO 1200 B BF A	3,815.00	40.00	95.37

## Input current:


Power (W)	Input current
40.00	0,292 - 0,137 A
40.00	0,292 - 0,137 A
40.00	0,292 - 0,137 A

## Photometric:



**Performa Pro 45W/  
74W/ 100W 60°**

## Product dimensions:



**Performa Pro 45W/  
74W/ 100W**

## Downloads:

[Go to downloads section](#)