



Slim

Linear Lighting

Slim is the perfect lighting solution for spaces that need uniform and versatile illumination. This linear luminaire is designed for quick and easy installation, thanks to its mechanical/electrical interconnectable system, available in two different sizes: 2ft and 4ft. This makes Slim an ideal choice for a wide variety of spaces, from small offices, to commercial spaces, etc.

It is the perfect solution for any space that needs uniform, efficient and versatile lighting.

Certifications:



Warranty:

5 Years

General technical data:

Light source	Built-in LED
Nominal luminous flux (lm)	2,600 - 5,850
System Efficacy (lm/W)	>130
CCT	3000K/ 4,000K
CRI	80
Beam angle	120°
Power	20W/ 36 W/ 45 W
Input voltage	127 - 277 V~
Input Frequency	50/60 Hz
Power factor	>0.90
Total Harmonic Distortion (THD)	<10%
Operating Temperature	-10 to 40 °C
Driver	Integrated
Control	0 - 10V
Lifespan / LED maintenance	50,000h L70
Housing	Aluminium
Lens material	Polycarbonate PC
Finish	Electrostatic painting
Color	White
IP	10
IK	04
Mounting type	Surface Recessed Suspended

Order information:



Code construction example:
UF 1052 B BN A

Application	Consec.	Color	CCT	Input Voltage	Power	Nominal luminousflux	CRI	Control	Dimensions	Installation
UF	1052	B- White	BN- 4000K	A- 127-277V~	36W	4,700	80	0-10V	51*51*1140mm	Recessed
	1053				45W	5,850			51*51*2372mm	Recessed
	4047				25W	2,600			51*51*680mm	Surface
	4048				36W.	4,700.			51*51*1140mm.	Surface
	4049				45W.	5,850.			51*51*2372mm.	Surface
	8021				25W.	2,600.			51*51*680mm.	Suspended
	8022				36W..	4,700..			51*51*1140mm..	Suspended
	8056				45W..	5,850..			51*51*2372mm..	Suspended


Energy efficiency:

CODE	Nominal luminous flux (lm)	Power (W)	System Efficacy (lm/W)
UF 1052 B BN A	4,680	36	130
UF 1053 B BN A	5,850	45	130
UF 4047 B BN A	2,600	25	104
UF 4048 B BN A	4,680	36	130
UF 4049 B BN A	5,850	45	130
UF 8021 B BN A	2,600	25	104
UF 8022 B BN A	4,680	36	130
UF 8056 B BN A	5,850	45	130

Input current:





Power (W)	Input current
36	0,278 - 0,145 A
45	0,353 - 0,174 A
25	0,152 - 0,092 A
36	0,278 - 0,145 A
45	0,353 - 0,174 A
25	0,152 - 0,092 A
36	0,278 - 0,145 A
45	0,353 - 0,174 A

Photometric:



Slim 20W/ 36W/ 45W



Product dimensions:



Slim 2ft Recessed

Slim 4ft Recessed

**Slim 2ft Surface/
Suspended**



**Slim 4ft Surface/
Suspended**

Downloads:

[Go to downloads section](#)