



## Urban City

### Contemporary design

Urban City is a pole-top luminaire with an aluminum injection molded body finished in graphite-colored micro-sprayed baked-on paint, with LED technology. Its contemporary design makes it suitable for urban pedestrian areas, parks, gardens and streets of private subdivisions.

Certifications:



Warranty:

5 Years

#### General technical data:

Light source	Built-in LED
Nominal luminous flux (lm)	9,100 - 13,450
System Efficacy (lm/W)	<105
CCT	4000K/ 5000K
CRI	80
Beam angle	Type IIM
Power	75W/ 80W/ 130W
Input voltage	127 - 277 V~
Input Frequency	50/60 Hz
Power factor	>0.90
Total Harmonic Distortion (THD)	<10%
Operating Temperature	-10 to 40 °C
Driver	Integrated
Control	0 - 10V
Lifespan / LED maintenance	50,000h L70
Housing	Aluminium
Lens material	PMMA
Finish	Electrostatic painting
Color	Grey
IP	65
IK	10
Mounting type	Pole

### Order information:



Code construction example:  
UU 9080 N BN A

Application	Consec.	Color	CCT	Input Voltage
UU	9080	N- Black	BN- 4000K	A- 127-277V~
	9086		BF- 5000K	
	9087		BF- 5000K.	

Power	Nominal luminous flux	CRI	Control	Beam Angle	Dimensions
80W	7,700	80	0-10V	120°	460*833mm
75W	8,250			Type IIM	
130W	13,400			Type IIM.	


## Energy efficiency:

CODE	Nominal luminous flux (lm)	Power (W)	System Efficacy (lm/W)
<b>UU 9080</b> N BN A	7,725	75	103
<b>UU 9086</b> N BF A	8,240	80	103
<b>UU 9087</b> N BF A	13,390	130	103

## Input current:


Power (W)	Input current
75	0.643-0.307 A
80	0,630 - 0,297 A
130	1.077-0.503 A

## Photometric:



Urban City Type IIM

## Product dimensions:



Urban City 75W/ 80W/  
130W

## Downloads:

[Go to downloads section](#)