

General technical data:



## Metroled

### Flush lighting

Linear luminaire designed to be installed at low height on the parapet of roads, the optical design seeks to generate a flush lighting effect on the vehicular surface, while the luminous effect on the perimeter of bridges or road distributors works as a great resource for visual orientation.

Certifications:

Warranty:

5 Years



Light source	Built-in LED
Nominal luminous flux (lm)	1,400
System Efficacy (lm/W)	>55
CCT	5000K
CRI	70
Beam angle	170*20°
Power	25W
Input voltage	127-277V~
Input Frequency	60 Hz
Power factor	> 0.9
Total Harmonic Distortion (THD)	< 10 %
Operating Temperature	-10 a 40 °C
Driver	Integrated
Control	ON/OFF
Lifespan / LED maintenance	50,000h L70
Housing	Aluminium
Lens material	PMMA (Acrylic)
Finish	Satin
IP	65
IK	10
Mounting type	Surface

### Order information:



Code construction example:  
UU 7161 F BF A

Application	Consec.	Color	CCT	Input Voltage
UU	7161	F- Grafito	BF- 5000K	A- 127-277V~

Power	Nominal luminous flux	CRI	Control	Beam angle	Dimensions
25W	1,400	70	ON/OFF	170*20°	763*120*171


### Energy efficiency:

CODE	Nominal luminous flux (lm)	Power (W)	System Efficacy (lm/W)
UU 7161 F BF A	1,397	25.3	55.2

### Input current:

Power (W)	Input current
25.3	0.196 - 0.090 A


## Photometric:



**Metroled 25W**

**170\*10°**

## Product dimensions:



**Metroled 25W**

Downloads:

[Go to downloads section](#)