



Softlight

Visual Comfort

Softlight is a LED ceiling luminaire whose aesthetic design responds to current architectural trends. It provides appropriate general light to improve the productivity of users in office and corporate spaces.

Certifications:



Warranty:

5 Years

General technical data:

Light source	Built-in LED
Nominal luminous flux (lm)	4,600
System Efficacy (lm/W)	>115
CCT	4000K
CRI	80
Beam angle	120°
Power	40W
Input voltage	127-277V~
Input Frequency	60 Hz
Power factor	> 0,9
Total Harmonic Distortion (THD)	< 10 %
Operating Temperature	-10 to 40 °C
Driver	Integrated
Control	0-10V
Lifespan / LED maintenance	50,000h L70
Housing	Steel
Lens material	PET (Polyethylene terephthalate)
Finish	Electrostatic painting
Color	White
IP	10
IK	04
Mounting type	Recessed

Order information:



Code construction example:
UF 1833 B BN A

Application	Consec.	Color	CCT	Input Voltage
UF	1833	B- White	BN- 4000K	A- 100-277V~

Power	Nominal luminous flux	CRI	Control	Beam angle	Dimensions
40W	4,600	80	0-10V	120°	605*605 mm


Energy efficiency:

CODE	Nominal luminous flux (lm)	Power (W)	System Efficacy (lm/W)
UF 1833 B BN A	4,632	39.50	117.27

Input current:


Power (W)	Input current
39.50	0,296 - 0,135 A

Photometric:



Softlight 40W 120°

Product dimensions:



Softlight 40W

Downloads:

[Go to downloads section](#)