



Softlight

Visual Comfort

Softlight is a LED ceiling luminaire whose aesthetic design responds to current architectural trends. It provides appropriate general light to improve the productivity of users in office and corporate spaces.

Certifications:



Warranty:

5 Years

General technical data:

| | |
|---------------------------------|----------------------------------|
| Light source | Built-in LED |
| Nominal luminous flux (lm) | 4,600 |
| System Efficacy (lm/W) | >115 |
| CCT | 4000K |
| CRI | 80 |
| Beam angle | 120° |
| Power | 40W |
| Input voltage | 127-277V~ |
| Input Frequency | 60 Hz |
| Power factor | > 0,9 |
| Total Harmonic Distortion (THD) | < 10 % |
| Operating Temperature | -10 to 40 °C |
| Driver | Integrated |
| Control | 0-10V |
| Lifespan / LED maintenance | 50,000h L70 |
| Housing | Steel |
| Lens material | PET (Polyethylene terephthalate) |
| Finish | Electrostatic painting |
| Color | White |
| IP | 10 |
| IK | 04 |
| Mounting type | Recessed |

Order information:



Code construction example:
UF 1833 B BN A

| Application | Consec. | Color | CCT | Input Voltage |
|-------------|---------|----------|-----------|---------------|
| UF | 1833 | B- White | BN- 4000K | A- 100-277V~ |

| Power | Nominal luminous flux | CRI | Control | Beam angle | Dimensions |
|-------|-----------------------|-----|---------|------------|------------|
| 40W | 4,600 | 80 | 0-10V | 120° | 605*605 mm |


Energy efficiency:

| CODE | Nominal luminous flux (lm) | Power (W) | System Efficacy (lm/W) |
|----------------|----------------------------|-----------|------------------------|
| UF 1833 B BN A | 4,632 | 39.50 | 117.27 |

Input current:


| Power (W) | Input current |
|-----------|-----------------|
| 39.50 | 0,296 - 0,135 A |

Photometric:



Softlight 40W 120°

Product dimensions:



Softlight 40W

Downloads:

[Go to downloads section](#)